McKissick® Oilfield Drilling Blocks

SELBY ENGINEERING & LIFTING SAFETY LTD.

Lifting Equipment and Height Safety Specialists

www.liftingsafety.co.uk sales@liftingsafety.co.uk

Tel: +44 (0) 1977 684 600 Fax: +44 (0) 1977 685 300






RP Style Traveling Blocks

- Capacities Available: 250, 350, 500, 750 and 1000 Tons
- Double row, pre-adjusted tapered bearings with seals.
- Blocks contain McKissick® Roll-Forged® sheaves with flame hardened grooves
 - Grooves are API profile
- Separate lubrication channel to each sheave.
- Easy opening guards for quick string-up (no bolts to pull out and lose).
- Bail design to adapt to comparable capacity drilling equipment
- Additional weights available upon request.
- Manufactured to the requirements of API 8C, including all documentation.
 - Each block is individually serialized for full traceability.
 - Furnished with Certificate of Conformance.
- Minimum design temperature of -20 degree C (-4 degree F).
- Standard top coat finish is safety orange enamel.
 - Other paint colors and systems are available on request.
 - Individual parts are primer coated on exposed surfaces.
- Block side plates can be drilled to adapt customer supplied equipment.
- Easy bail pin removal.
- All sizes are RFID EQUIPPED.





RP Style Drilling Blocks

Working	Sheave	Standard Wire Rope	Weight	Dimensions (in.)										
Load Limit Tons	Diameter (in.)	Size (in.)*	Each (lbs.)	Α	В	С	D	E	F	н	J	К	L	М
250	36	1-1/8	5600	74.00	63.00	11.00	36.00	39.00	24.25	5.00	2.50	3.50	10.88	7.94
250	42	1-1/8	7050	80.00	69.00	11.00	42.00	44.00	24.25	5.00	2.50	3.50	10.88	7.94
350	42	1-1/4	7150	80.00	69.00	11.00	42.00	44.00	24.25	5.00	2.50	3.50	10.88	7.94
500	60	1-3/8	16100	98.25	84.25	14.00	60.00	61.50	32.75	6.00	3.50	4.00	15.00	12.75
750	60	1-1/2	21800	107.25	92.25	15.00	60.00	61.50	39.00	9.00	4.50	5.00	18.50	17.00
1000	72	1-3/4	38500	127.25	109.25	18.00	72.00	74.00	48.25	9.00	5.00	6.25	19.75	21.25

^{*} Additional wire rope sizes are available.