

RGL16

TWIN LEG WEBBING ADJUSTABLE LANYARD & SHOCK ABSORBER RGL16



The RGL16 is a twin leg fall arrest lanyard; the extra leg allows movement between anchorage points by means of double clipping. This system is generally used for tower climbing, steel erecting, scaffolding and maintenance on open structures.

When used in conjunction with two girder slings (RGK26), the RGL16 can be used as a means of progression through suitable structures where no fixed lifeline or eye-bolts are available. The lanyard length can be adjusted to suit the application. Potential trip hazards can be avoided and potential free fall distance can be reduced which is less possible with a non-adjusting lanyard.

EN 355:2002

Material:	26mm RIDGE Protect anti-bacterial polyester*
Fittings:	17mm steel screwgate karabiner (RGK1) 2 x steel adjusters
Max arrest force:	<6kN
Length (s)	1.2m - 1.8m (including connectors)

FEATURES



Steel Adjusters



Shock Absorber



RIDGEGEAR LIMITED Nelson Street, Leek, Staffordshire, ST13 6BB +44 (0)1538 384 108

sales@ridgegear.com

ridgegear.com

©2023 RIDGEGEAR Limited. All the information and imagery within this data sheet is subject to copyright. While we make every effort to ensure all the information here is correct and up-to-date, it is always worth checking with us before ordering. We reserve the right to change product specifications when necessary without prior notice.



Q05822