



## TITAN AUTOMATIC ROPE GRAB - 10M

### Product use

The automatique rope grab and anchorage line is designed to prevent workers from falling during ascent or descent. It is particularly useful on sloping roofs where retractable lifelines may react too slowly. The automatic rope grab locks onto the rope in the event of a fall, arresting a fall within centimeters thus reducing the fall arrest forces and facilitating rescue. The rope is 10-meter long.

### Technical description

#### Rope

Raw material: Ø12mm Polyamide  
Standard: EN 696  
Breaking strength: > 2940 daN

#### Karabiner

Raw material: Zinc-plated steel  
Standard: EN 362  
Opening : 18 mm  
Breaking strength: > 2500 daN

#### Automatic snap hook

Raw material: Chromate steel  
Standard: EN 362  
Opening : 20 mm

#### Standards

EN 353-2

### Additional informations

Also exists in 15, 20 and 30m.

### Technical specifications and norms

European directive :  
89/686/CEE

Norms :

EC type attestation :

Quality Assurance

Certification number :

Marking :

[click address to go to....](#)

# TITAN AUTOMATIC ROPE GRAB - 10M

The supplier or its legal representative supplier settled in the European community :

**MILLER**

declares that the new Individual Protection Equipment described hereafter :

Designation :

**TITAN Automatic Rope Grab - 10m**

Article code :

**1011190**

is in conformity with Directive dispositions 89/686/CEE.

This PPE has been the object of the EC attestation type :

delivered by :

Made on the : **06/01/2006**

at :

Division : **Fall Protection**

By :

[click address to go to....](#)