SELBY ENGINEERING & LIFTING SAFETY LTD. Lifting Equipment and Height Safety Specialists www.liftingsafety.co.uk sales@liftingsafety.co.uk Tel: +44 (0) 1977 684 600 Fax: +44 (0) 1977 685 300

D FALL PROTECTION RM Harness - Size M

REF. 1003439



GENERAL DATA

Division : Fall Protection Family : Fall Protection Range : Harness Brand formerly known as : MILLER Business Countries EMEA Activity Domains : Telecoms • Utilities

Product Use :

Full body harness with elasticated shoulder strap, front anchorage loop, back D-ring and positioning belt.

5 SPERIAN

PRODUCT ADVANTAGES

Feature :

Rear and sternal anchorage for fall arrest, ventral anchorage loops (access and suspension) and side anchorage (work-positioning).

Patented elasticated webbing on the shoulder straps stretches with the user for greater freedom of movement and comfort with reduced fatigue.

Lightweight and easy-to-fit with quick-fixing automatic buckles

Greater productivity thanks to the padded belt and leg straps that provide excellent support for work in suspension. **Benefit :**

The RM harness is a light and comfortable full body harness. One of its main features is a very easy setup, thanks to its 3 quick-lock buckles (thighs + belt). Work in suspension is made more comfortable with a design that applies the load on the thighs and not on the entire harness.

The perfect compromise between freedom of movement for access and excellent support for suspension.

Its versatility, ease of use, as well as its elasticated webbings allow multiple applications, for all kinds of people working at height.

TECHNICAL DESCRIPTION

Webbings

Webbing : Shoulder straps Material : Polyamide & elastomer Width (mm) : 45 Breaking Strength : >2200 daN

Dorsal D-Ring

Raw Material : stainless steel

Dimensions : 54x62x7mm

Breaking Strength : > 4000 daN

Adjustement Buckles

Raw Material : aluminum Breaking Strength : > 750 daN

<u>Belt</u>

Side D-Rings : Aluminium alloy Dimensions : 60x64x7mm

Back Pad

Material : black polyester foam

5 SPERIAN

Performance

Operating Temperature : -30°C to +50°C

General Information

Weight (kg) : 1.58 kg

Size : M/L Complementary Information :

Automatic buckles : stainless steel & aluminum Breaking strength > 900 daN

ADDITIONAL INFORMATION

User manual number : 90004212

CERTIFICATION AND CONFORMITY

European Directives : 89/686/EEC

EC Category PPE* : Class 3

Standards : EN358 / EN361

Quality Assurance : ISO 9001 / 2000

EC Certification Number : 333

EC Attestation Number : 0082/490/160/11/99/0404

Laboratory : APAVE Lyonnaise

*PPE : Personal Protective Equipment

5 SPERIAN

EC CONFORMITY DECLARATION

The manufacturer or its legal representative supplier settled in the European Community: Miller by Sperian

<u>Declares that the next Personal Protective Equipment described here after is in conformity with the provisions of</u> <u>Council Directive 89/686/CEE:</u>

Designation: RM Harness - Size M

Reference: 1003439

Standard(s): EN358 EN361

This PPE is the object of the above EC attestation type: 0082/490/160/11/99/0404

Delivered by:

APAVE Lyonnaise

177 route de Saint-Bel BP 3

69811 TASSIN CEDEX

France

Made at Vierzon, on the 06/15/2007 By: Yves Depin Division: Fall Protection

Det

"CE" Declaration

The manufacturer :	BACOU DALLOZ VIERZON
	35/37 rue de la Bidauderie
	18100 VIERZON

Declare that the next PPE described hereafter :

standard EN361

SAP reference1003439Old reference708251

item HARNAIS REMONTEE MECANIQUE PT/MT EC type examination :

0082/490/160/11/99/0404 ext.

Is in conformity with the provisions of Council Directive 89/686/EEC and is the subject of the above EC type examination certificate delivered by:

APAVE 177 Route de Saint Bel BP3 69811 TASSIN CEDEX

And is subject to the procedure set out in Article 11B of Directive 89/686/EEC under the supervision of the notified body :

N° 0333 AFAQ/AFNOR CERTIFICATION 116 Avenue Aristide Briand 92224 BAGNEUX CEDEX

> Fait à Vierzon le, 01/12/2003 Par : T.juillet Fonction: Plant Manager

Signature: