## National Hydraulic Swaging Machines

National offers the highest quality and most complete line of Hydraulic Swaging Machines specifically designed to be used to swage fittings on wire rope.

#### 3 Capacities to Fit your Requirements

500 Tons 1000 Tons 1500 Tons





1500 Ton Hydraulic Swaging Machines
Approximate weight 34,500 lbs. Overall height 8 ft. 6 in.
Fast advance and retract speed.
Automatic slow, precision swaging speed.

The following features of National Hydraulic Swaging Machines offer a number of advantages for high production sling shops:

- A dual hydraulic system which combines the use of high speed and low pressure to bring dies into position; and the low speed and high pressure necessary for ideal swaging control.
- Adjustable tonnage control, so tonnage can be set to match die block Working Load Limit.
- Four column wide stance which provides the operator ample working clearance between columns and a large area for in-process sling storage.
- Vertical swage action which gives an equalized press on the fitting to produce uniform high quality.
- Self locating spring locks snap the shoe-type dies into place for quick set-up and change.
- The National four column wide stance Hydraulic Swaging Machines, each equipped with an up-acting ram, have two side cylinders for fast approach and return of the main ram. They come in three swaging capacities.
- 500 ton (4450 kN)
- 1000 ton (8900 kN)
- 1500 ton (13350 kN)

### **Swaging Machine Capacity Chart for Swage Sleeves, Ferrules & Buttons**

| Hydraulic<br>Swaging |                   | Die                                     | Largest Fitting Allowed<br>to be Swaged<br>(in.) |                 |                   |                  |
|----------------------|-------------------|-----------------------------------------|--------------------------------------------------|-----------------|-------------------|------------------|
| Machine<br>Size      | Swaging<br>Method | Size<br>(in.)                           | S-505<br>Sleeve                                  | S-506<br>Sleeve | S-510<br>Ferrules | S-409<br>Buttons |
| 500 Ton              | Full Die          | 2-1/2 x 5 Mark Series<br>4 x 7<br>5 x 7 | 1-1/2                                            | 1-1/4*          | 9/16*             | 7/8*             |
| 1000 Ton             | Full Die          | 4 x 7<br>5 x 7                          | 2-1/2                                            | 1-1/4*          | 9/16*             | 1-1/4*           |
| 1500 Ton             | Full Die          | 5 x 7<br>6 x 12                         | 3-1/2                                            | 1-1/4*          | 9/16*             | 1-1/4*           |
| 3000 Ton             | Full Die          | 6 x 12                                  | 4-1/2                                            | 1-1/4*          | 9/16*             | 1-1/4*           |

<sup>\*</sup> Largest size fitting available.

# NOTE: For special applications or conditions, contact Crosby National at (501) 982-3112.

## Swaging Machine Capacity Chart for S-501 & S-502 Swage Sockets

| 8                                       |                   |                                         |                                                     |  |  |
|-----------------------------------------|-------------------|-----------------------------------------|-----------------------------------------------------|--|--|
| Hydraulic<br>Swaging<br>Machine<br>Size | Swaging<br>Method | Die<br>Size<br>(in.)                    | Largest Fitting<br>Allowed to be<br>Swaged<br>(in.) |  |  |
| 500 Ton                                 | Full Shank        | 2-1/2 x 5 Mark Series<br>4 x 7<br>5 x 7 | 3/4                                                 |  |  |
|                                         | Progressive       | 4 x 7<br>5 x 7                          | 1-1/4                                               |  |  |
| 1000 Ton                                | Full Shank        | 4 x 7<br>5 x 7                          | 1                                                   |  |  |
|                                         | Progressive       | 4 x 7<br>5 x 7                          | 1-1/2                                               |  |  |
| 1500 Ton                                | Full Shank        | 5 x 7<br>6 x 12                         | 1-1/4                                               |  |  |
|                                         | Progressive       | 5 x 7<br>6 x 12                         | 2                                                   |  |  |
| 3000 Ton                                | Full Shank        | 6 x 12                                  | 2                                                   |  |  |
|                                         | Progressive       | 6 x 12                                  | 2-1/4                                               |  |  |

<sup>\*</sup> Largest size fitting available.