

Crosby Grade 100 Clevis Hooks

Fatigue Rated

"QT"
QUENCHED & TEMPERED

QUIC-CHECK®


Crosby 8/10™

A-1339



- Forged Alloy Steel - Quenched and Tempered.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Each hook has a Product Identification Code (PIC) for material traceability, along with the size and the name Crosby & U.S.A. in raised letters.
- Hoist hooks incorporate two types of strategically placed markings forged into the product which address two (2) QUIC-CHECK® features : Deformation Indicators and Angle Indicators.
- Low profile hook tip.
- New integrated latch (S-4320/S-4339) meets the world standard for lifting.
 - Heavy duty stamped latch interlocks with the hook tip.
 - High cycle, long life spring.
 - When secured with the proper cotter pin through the hole in the tip of hook, meets the intent of OSHA Rule 1926.550(g) for personnel lifting.
- Suitable for use with Grade 100 chain in overhead lifting applications as long as hook is Proof Tested as part of the chain sling assembly or as an individual component. Per ANSI B30.9-1.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- "Look for the Platinum Color - Crosby Grade 100 Alloy Products."

A-1339 Clevis Sling Hook



Chain Size		Working Load Limit (lbs.)*	Hook ID Code	A-1339 Stock No.	Weight Each (lbs.)	Dimensions (in.)						S-4320 Rep. Latch Stock No.	S-4339 Rep. Latch Stock No.	
(in.)	(mm)					D	G	J	L	M	R			AA
-	6	3200	DA	1048982	0.64	2.86	0.73	0.93	4.21	0.63	2.95	1.50	1096325	-
1/4	7	4300	HA	1048991	1.58	3.86	1.04	1.19	5.67	0.75	3.97	2.00	1096468	-
5/16	8	5700	HA	1049000	1.57	3.86	1.04	1.19	5.67	0.75	3.95	2.00	1096468	-
3/8	10	8800	IA	1049009	2.58	4.38	1.19	1.53	6.75	1.00	4.71	2.50	1096515	-
1/2	13	15000	JA	1049018	5.28	5.60	1.44	1.78	8.38	1.17	5.89	3.00	1096562	-
5/8	16	22600	KA	1049027	9.81	6.76	1.89	2.41	10.21	1.44	6.97	4.00	1096609	-
3/4	18-20	35300	-	1049036	18.3	8.31	2.83	2.69	13.07	1.97	8.00	4.50	-	1048714
7/8	22-23	44100	-	1049045	24.6	9.17	3.07	3.05	13.98	1.97	8.76	5.00	-	1048732

* Ultimate Load is 4 times the Working Load Limit.