

Lebus® Snatch Blocks



Fatigue Rated



SEE APPLICATION AND WARNING INFORMATION

Para Español: www.thecrosbygroup.com

On Pages 342-349

L-160 Series Heavy Duty Snatch Blocks

- Hook is Forged Alloy Steel — Quenched and Tempered.
- Designed for fast, efficient line changes.
- All parts are forged.
- Beaded side plate prevents rope from jamming.
- Available with hook, shackle or tailboard (pin only).
- Can be furnished with hook latch.
- Blocks furnished with dual rated wireline sheaves.
- Fatigue Rated.



L-5-H



L-5-S



L-5-T

Block No.	Bearing Code	L-160 Stock No.	Fitting	Sheave Diam. (in.)	Working Load Limit (t)*	Wire Rope Size (in.)	Weight Each (lbs.)	Rep. Sheave Stock No.	Rep. Latch Stock No.
L-5-H	BB	599506	Hook	5	6	3/8 - 1/2	15	592095	1096468
L-5-H	RB	599515	Hook	5	6	3/8 - 1/2	15	592157	1096468
L-5-S	BB	599524	Shackle	5	6	3/8 - 1/2	15	592095	-
L-5-S	RB	599533	Shackle	5	6	3/8 - 1/2	15	592157	-
L-5-T	BB	599542	Tailboard	5	6	3/8 - 1/2	10	592095	-
L-5-T	RB	599551	Tailboard	5	6	3/8 - 1/2	10	592157	-
L-6-H	BB	599560	Hook	5-7/8	12	5/8 - 3/4	32	592175	1096609
L-6-H	RB	599579	Hook	5-7/8	12	5/8 - 3/4	32	592255	1096609
L-6-S	BB	599588	Shackle	5-7/8	12	5/8 - 3/4	30	592175	-
L-6-S	RB	599597	Shackle	5-7/8	12	5/8 - 3/4	30	592255	-
L-6-T	BB	599604	Tailboard	5-7/8	12	5/8 - 3/4	18	592175	-
L-6-T	RB	599613	Tailboard	5-7/8	12	5/8 - 3/4	18	592255	-

* Ultimate Load is 4 times the Working Load Limit.

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing, and wire rope size.