

# Western Blocks for Manila Rope

**SELBY ENGINEERING & LIFTING SAFETY LTD.**  
 Lifting Equipment and Height Safety Specialists  
 www.liftingsafety.co.uk sales@liftingsafety.co.uk  
 Tel: +44 (0) 1977 684 600 Fax: +44 (0) 1977 685 300



**SEE APPLICATION AND WARNING INFORMATION**

Para Español: www.thecrosbygroup.com On Pages 342-349



**T-350-C**

## Gin Blocks for Manila Rope

- For light hoisting by Roofers and Contractors.
- Furnished with drop forged swivel latch hooks.

Block Size (in.)	Fitting	Gin Block Stock No.			Sheave Size (in.)			Manila Rope Size (in.)	Working Load Limit (lbs.)*	Weight Each (lbs.)
		T-350-B	T-350-R	T-350-C	Outside Diam.	Rim Thickness	Bearing Diam.			
8	T	710403	710207	710001	8.00	1.25	.75	7/8	1000	9.0
10	T	710421	710225	710029	10.00	1.25	.88	1	1000	9.8
12	T	710449	710243	710047	12.00	1.38	.88	1	1000	12.7

\* Ultimate Load is 3 times the Working Load Limit.

Bearing Code: B-Self Lubricating Bronze Bushed, R-Roller Bearing, C-Common Iron



**HS-130-B SINGLE**

## Painter's Supply Blocks for Manila Rope

- Furnished in Bronze Bushed.
- For 3/4" Manila Rope.
- Steel Parts are Galvanized.
- Furnished with Loose Side Hooks with Latch or Shackle.

Block Size (in.)	Fitting	Single Sheave Blocks	Double Sheave Blocks	
		HS-130 B* Stock No.	HS-135 B* Stock No.	P-135 B* Stock No.
6	HS	601236	631034	-
6	HS	-	-	8004829

\* Bearing Code: B-Self Lubricating Bronze Bushed

Block Size (in.)	Sheave Size (in.)			Manila Rope Size (in.)	Resultant Working Load Limit (lbs.)*		Weight Each (lbs.)	
	Outside Diam.	Rim Thickness	Center Pin Dia.		130 Single	135 Double	130 Single	135 Double
6	3.50	1.00	.75	3/4	1800	2500	5	10

\* Ultimate Load is 4 times the Resultant Working Load Limit.