



## RG10 AUTOMATIC SELF DESCENDER

### Product use

RG 10 regulated descender equipped with GO60 hook and rope clamp

### Technical description

**Main device :**

Case : Aluminium  
 Mechanism : Stainless steel

Breaking strength : > 12 KN  
 Descent speed : 1.5 meter/second  
 Temperature : -30°C to +50°C

Maximum length of use : 300m

Weight : 2.829 Kg

**Maillon Rapide :**

Raw material: Steel finishing with zinc  
 Breaking strength: > 2500 daN

**Automatic snap hook GO60**

Raw material : Aluminium  
 Standard : EN 362  
 Breaking strength : > 2000 daN

### Technical specifications and standard

**European directive :**  
89/686/CEE

**Norms :**  
EN341

**EC type attestation :**  
98 1 0392/008-0115

**Quality Assurance**  
AFAQ: ISO 9001 : Version 2000

**Certification number :**  
0333 AFAQ/CTH

**Marking :**  
MILLER



### Additional information

click address to go to...



# RG10 AUTOMATIC SELF DESCENDER

The supplier or its legal representative supplier settled in the European community :

**MILLER**

declares that the new Individual Protection Equipment described hereafter :

Designation :

**RG10 Automatic Self Descender**

Article code :

**10 030 42**

is in conformity with Directive dispositions 89/686/CEE.

This PPE has been the object of the EC attestation type :

**98 1 0392/008-0115**

delivered by :

**D.M.T.**

**Zertifizierungsstelle**

**45307**

**ESSEN**

**Germany**

Identified by the number :

Made on the : **16/09/2004**

at : **Vierzon**

Division : **Fall Protection**

By : **Frederic GUICHARD**

[click address to go to...](#)

