



SELBY ENGINEERING & LIFTING SAFETY LTD.
Lifting Equipment and Height Safety Specialists
www.liftingsafety.co.uk sales@liftingsafety.co.uk
Tel: +44 (0) 1977 684 600 Fax: +44 (0) 1977 685 300



DELTA™ II - FULL BODY FALL ARREST HARNESS



THE DELTA™ II LINE FEATURES A NEW NO-TANGLE BACK PAD WITH A STAND-UP DORSAL D-RING FOR EASIER AND QUICKER CONNECTIONS!

- The spring loaded stand-up back D-ring* ensures fast, easy and safe connections.
- The exclusive Delta No-Tangle® design holds the shape of the harness for added comfort and ease-of-use - it greatly increases worker acceptance while reducing improper usage.
- Optional color coded quick-connect buckles make it easy to put on and fit every time.
- Add the optional Delta™ Comfort Pad for wrap-around comfort enhancing worker productivity and compliance - it's even removable and washable!
- Meets or exceeds all applicable industry standards including OSHA, the stringent ANSI Z359.1, and CE EN361 and EN358.

DELTA™ II - FULL BODY FALL ARREST HARNESS



DBI-SALA harnesses have a reputation for quality, durability and excellent features! The recently CE certified Delta II harness range continues to build on this reputation with a host of new features.

Features include a unique back pad with a stand-up, spring-loaded back D-ring and optional patented DBI-SALA quick connect buckles. Our exclusive Delta No-Tangle® Pad holds the shape of the harness, adds comfort and makes the harness easier to don. And every Delta™ harness combines maximum comfort, freedom of movement and ease-of-use. Each harness also incorporates special web keepers which tuck excess webbing neatly away.

Fast, Easy and Safe Connections The Delta pad now incorporates a patented integrated spring-loaded "stand-up" dorsal D-ring. This provides the user with quick and safe connections enhancing ease-of-use and worker productivity.

Optional Quick-Connect Buckles easily adjust, engage and disengage with only one hand. These patented quick-connect buckles are also color-coded, making it easy to don the harness correctly every time.

Wrap-Around Comfort With the addition of the optional Delta™ Comfort Back Pad, your harness will be comfortable for longer hours of wear with less fatigue. It provides the comfort of a luxury harness at a midlevel harness price! The padding on the shoulders distributes the weight and keeps the pressure off, even when wearing heavy tool belts. Padding is removable and completely washable!



Delta II Harness Models

KB11109117 : Single point rear D-ring

Pass Through Buckles :

KB11109117=UNIV, KB11109118=SM, KB11109119=XL

Quick-Connect Buckles :

KB11110615=UNIV, KB11110616=SM, KB11110617=XL

KB11107527 : Single point rear D-ring with work positioning belt

Pass Through Buckles :

KB11107527=UNIV, KB11107528=SM, KB11107529=XL

Quick-Connect Buckles :

KB11110579=UNIV, KB11110580=SM, KB11110581=XL

KB11101288 : 2 point front + rear D-ring

Pass Through Buckles :

KB11101288=UNIV, KB11101289=SM, KB11101290=XL

Quick-Connect Buckles :

KB11101319=UNIV, KB11101320=SM, KB11101321=XL

KB11101294 : 2 point front + rear D-ring with work positioning belt (shown above)

Pass Through Buckles :

KB11101294=UNIV, KB11101295=SM, KB11101296=XL

Quick-Connect Buckles :

KB11101312=UNIV, KB11101313=SM, KB11101314=XL

Specifications :

- **Webbing** - 45mm width, 100% Polyester, Minimum Breaking Strength >2600 daN
- **Optional Quick Connect buckles** - Minimum Breaking Strength >1700 daN, Heat treated alloy steel, zinc plating with black e-coat finish on waist, chest, clear chromate finish on legs.
- **Thread** - High strength, 100% Polyester

- **D-rings** - Minimum Breaking Strength >2200 daN, Heat treated forged alloy steel, yellow chromate zinc plating finish
- Meets or exceeds all applicable industry standards including OSHA, ANSI, the stringent ANSI Z359.1, and CE EN361 and EN358.

Capital Safety

Europe, Middle East, Africa : +33 (0) 497 10 00 10 • Northern Europe : +44 (0) 1928 57 1324 • USA : 800.328.6146

Canada : 800.387.7484 • Asia : + 852 2992 0381 • Australia/New Zealand : 800 245 002

www.capitalsafety.com • info@capitalsafety.com

Form: A0127EN rev: A