



Ref : KB11111630, KB11111631, KB11111632, KB11111633

## Delta™ II Derrick Harness

Designed especially for the oil extraction industry, this work horse is built for this harsh environment to offer the longevity and performance to the user.

Rear fall arrest 40cm extension for ease of connecting of SRL

Mating buckles for connection of an optional derrick belt

Rear fall arrest D-ring

Keeper strap for D extension when not in use

Front fall arrest D-ring for vertical systems (ladder climbing)

Mating buckles for connection of an optional Seat sling

*i*safe™ equipped

Complies with CE - EN361/EN358 OSHA, ANSI and the stringent ANSI Z359

D-ring for positioning

Tongue buckle leg straps for fast and easy donning

Keeper strap

**Especially designed** for the oil extraction worker. It includes connection for optional derrick belt which provides the worker with restraint and comfort with the large frontal pad while positioning for the next drilling pipe. Alternatively on the rear of the harnesses belt there is a D connection point.

**Web seat sling** as an option to reduce fatigue, whilst in suspension or work position and for use with man riding systems. Mating buckles on the belt of the harness allow for the connection of a web seat sling.

### Options:

**Webbing Seat Sling:** KB01150082 (SM), KB01150083 (MED), KB01150084 (LG)  
**Derrick Board Belt:** KB01000570

### Specifications:

- **Delta™ II derrick Harness models:** KB11111630 (SM), KB11111631 (MED), KB11111632 (LG), KB11111633 (XL)
- **Webbing:** 45mm width, 100% Polyester, Minimum Breaking Strength >2600 daN
- **Thread:** High strength, 100% Polyester
- **D-rings:** Minimum Breaking Strength >2200 daN, Heat treated forged alloy steel, clear chromate zinc plating finish
- **Hardware:** Heat treated forged alloy steel, yellow chromate zinc plating finish
- **i-Safe™ equipped:** Harness individual serially numbered
- **Net weight:** 3130g (MEDIUM SIZE)
- **System attachment:** points breaking Strength >15KN
- **Standards:** CE - EN361+EN358, OSHA and ANSI (ANSI Z359)