

Portable Aluminium Gantry Crane with Adjustable Feet, 1000kg, 1500kg or 2000kg x up to 5m Beam length (6 Options)

Model: AGC-2741

Lightweight aluminium gantry crane suitable for uneven / rough terrain.



Fully Retracted



Fully Expanded



Component Dimensions

SELBY ENGINEERING AND LIFTING SAFETY LTD. TEL: +44 (0) 1977 684 600
THIS DOCUMENT IS PROPERTY OF SELBY ENGINEERING AND LIFTING SAFETY LTD. UNDER NO CIRCUMSTANCES MUST THIS DOCUMENT BE REDISTRIBUTED, EDITED OR USED AS BASIS FOR COMPETITIVE TENDER

LIFTINGSAFETY.CO.UK

THIS DOCUMENT IS PROPERTY OF SELBY ENGINEERING AND LIFTING SAFETY LTD. UNDER NO CIRCUMSTANCES MUST THIS DOCUMENT BE REDISTRIBUTED, EDITED OR USED AS BASIS FOR COMPETITIVE TENDER

SELBY ENGINEERING AND LIFTING SAFETY LTD. TEL: +44 (0) 1977 684 600

Our AGC-2741 range of Aluminium mobile lifting gantries are all extremely lightweight and portable covering capacities from 1000kg, 1500kg and 2000kg. The design is fully adjustable in width between the vertical uprights and height adjustable both in the vertical column and all four leg posts.

These gantries provide a cost effective portable lifting solution and are made in Germany, Western Europe.

Delivery lead time for the standard height gantries is usually only 1-2 days though generally never more than two weeks from order as a shipment is received every 2 weeks from Germany; the Extra tall gantries are made to order and so the lead time is a little longer at about 3 weeks lead time..

The most cost effective solutions will be to utilise our standard range / sizes of aluminium lifting gantry though if this is not a possibility then we can quote for the supply of modified (bespoke) / special alloy lifting gantry to suit your specification.

Castors?

We offer the gantry range with-out castors fitted and all the dimensions below reflect no castors fitted. We can supply castor's that will fit the pre-drilled gantry feet at additional cost. Before you fit these and use the lifting gantry you must fist carry out your own risk assessment and method statement and then it is your responsibility to conclude that castors are appropriate and suitable for that particular lift and that the lift is being conducted by a competent person. The castors are individually load rated at 750kg and are all swivel with two braked. We do not recommend that the gantry is moved under load. (We can supply all braked and fitted with directional locking castors if required).

Features

- Lightweight options at 1000kg, 1500kg and 2000kg. Beam lengths available up to 5 metre long.
(special made to order gantries available on request)
- Supplied with push travel beam trolley (load trolley)
- Easy to transport and erect, entire crane made of light weight aluminium (alloy).
- Supplied with optional swivel, braked castors.
- Extremely competitive priced.
- Each support leg is fitted with a large base plate (helps stop sinking in to softer ground) and can be individually adjusted for working on uneven ground. (all terrain / rough terrain capable)
- Working width infinitely adjustable.
 - Split type only: Running rail and lateral parts with folding up and disassembling possibility.

Specifications

Part N°	Load Capacity (kg)	Beam Length (mm)	Total Weight (kg)	Overall Width	Max. Height (& under beam)	Min. Height (& under beam)	Height Adjustment	I beam depth
2741-B	1000kg	5000	130	1715mm	3520mm (3220mm)	2295mm (1995mm)	1225mm	300mm
2741-C	1000kg	5000	TBA	1715mm	4300mm (4000mm)	3075mm (2775mm)	1225mm	300mm
2741-D	1500kg	4000	124	1715mm	3520mm (3220mm)	2295mm (1995mm)	1225mm	300mm
2741-E	1500kg	4000	TBA	1715mm	4300mm (4000mm)	3075mm (2775mm)	1225mm	300mm
2741-G	2000kg	4000	139	1715mm	3520mm (3220mm)	2295mm (1995mm)	1225mm	300mm
2741-H	2000kg	4000	TBA	1715mm	4300mm (4000mm)	3075mm (2775mm)	1225mm	300mm

Gantry Close-up Images

	Top Beam adjustment, easily adjustable lifting beam width		Top Side View of the Gantry Legs Showing vertical height adjustment
	Gantry Legs showing height adjustable feet posts. Particularly suitable for uneven ground		Gantry Base Plate showing no Castor's fitted (though pre-drilled) large base plate helps prevent penetration in to soft ground
	Optional Castors, All Swivel, two braked, 200mm high, brown polyurethane tyre on cast iron wheel		