

**technical sheet**

**Pallet trucks "PIONEER™" range  
W.L.L. : 1 to 3 t**

ref. : **2063 GB**  
 rev. n° : **1**  
 date : **06/08**  
 page : **1/1**

**Robustness :**

- Sturdy high resistance steel chassis and forks, welded on template
- High efficiency pump with long life piston
- Overloads protection

**Quality :**

- Chromium-plated piston
- greased for life bearings
- Axles fitted with greased nipples
- Protection by an acrylic paint applied after sand blaster treatment

**Ergonomics :**

- Control lever with three positions, well protected inside the rounded handle of the steering column
- Very precise control for lowering loads
- Automatic return of drag bar to vertical position
- Steering wheels and fork rollers with a polyurethane tread for a good loading capacity and minimum effort to move



**Specifications**

Type of product	W.L.L. kg	Total length mm	Total width mm	Total height mm	Length of forks mm	Width of forks mm	Distance between forks mm	Minimum height of lift mm	Maximum height of lift mm	Total weight kg	Front wheel dims mm	Steering wheel dims mm
PIONEER™ SD.	2000	1500	550	1180	1150	150	250	74	190	82	60X72	180X50
PIONEER™ SD.	2500	1500	550	1180	1150	150	250	74	190	87,5	60X72	180X50
PIONEER™ SD.	3000	1500	550	1180	1150	150	250	74	190	88	60X72	180X50
PIONEER™ SP.	2000	1500	550	1180	1150	150	250	84	200	84,5	70X80	180X50
PIONEER™ SP.	2500	1500	550	1180	1150	150	250	84	200	87	70X80	180X50
PIONEER™ SP.	3000	1500	550	1180	1150	150	250	84	200	87,5	70X80	180X50
QUICK-LIFT	2000	1500	550	1180	1150	150	250	74	190	83,5	60X72	166X70
HI-LIFT	1000	1535	540	1180	1150	162	116	90	800	107	50X80	180X50
PIONNER™	2000	1350	550	1180	900	150	250	74	190	80	60X72	180X50



 matériel conforme aux directives CE