

# Yale®

## Hand chain hoist

### Yalelift IT



Illustrated rubber buffers  
optionally available!

Hand chain hoist  
with integrated  
push type trolley  
model *Yalelift ITP*

Capacities 500 - 5.000 kg

Hand chain hoist  
with integrated  
geared type trolley  
model *Yalelift ITG*

Capacities 500 - 5.000 kg

The combination of the *Yalelift 360* with a low headroom manual trolley provides even more flexibility in the application of the *Yalelift 360*.

- All units of this series up to a capacity of 3.000 kg are provided with single chain fall and the min. headroom (Dim. A) has been further reduced. Ideal for applications with low ceilings and limited headroom.
- The manual trolleys are adjustable to fit a wide range of beam profiles (e.g. INP, IPE, IPB). Depending on the beam flange width an adjustment up to 300 mm can be made easily.
- The trolley wheels are designed for a max. beam profile incline of 14 % (DIN 1025 - part 1), excellent rolling features are guaranteed by pre-lubricated, encapsulated ball bearings.
- Anti-tilt and anti-drop devices are standard.
- A subsequent conversion of a *Yalelift 360* into a *Yalelift IT* with integrated trolley is easily possible at any time.

Optional equipment and accessories  
are given on pages 22 and 23!