

WIRELOCK®

SELBY ENGINEERING & LIFTING SAFETY LTD.
 Lifting Equipment and Height Safety Specialists
 www.liftingsafety.co.uk sales@liftingsafety.co.uk
 Tel: +44 (0) 1977 684 600 Fax: +44 (0) 1977 685 300

RESIN FOR SPELTER SOCKETS NOT AVAILABLE IN CANADA

Note: For use on 416, 417, 427 and 517 spelter sockets only.

- 100% termination efficiency.
- Temperature operating range is -65° F to +240° F.
- Ideal for on site applications.
- No hazardous molten metal.
- Improved fatigue life.
- Pouring temperature without booster pack is 48° F to 110° F.
- One booster pack if pouring temperature is 35° F to 48° F.
- Two booster packs if pouring temperature is 27° F to 35° F.
- Refer to WIRELOCK® Technical Manual for more information.



SEE APPLICATION AND WARNING INFORMATION
 Para Español: www.thecrosbygroup.com On Pages 56 - 57

Approvals

Lloyds Register of Shipping
 Det Norske Veritas (DNV)
 United States Coast Guard
 Registro Italiano Navale
 Germanischer Lloyd
 United States Navy
 American Bureau of Shipping.



U.S. Department of Transportation
 United States Coast Guard



WIRELOCK® W416-7 Socket Compound

W416-7 Kits				Booster Pack
Kit Size	Kit Per Case	Stock No.	Weight Each (lbs.)	Stock No.
100	20	1039602	.62	1039603
250	12	1039604	1.25	1039605
500	12	1039606	2.54	1039607
1000	12	1039608	4.59	1039609
2000	12	1039610	9.00	1039611

Guide to amount WIRELOCK® Required

Wire Rope Size		WIRELOCK® Required (cc)	Wire Rope Size		WIRELOCK® (cc)
(in.)	(mm)		(in.)	(mm)	
1/4	6-7	9	1-3/4	44	700
5/16	8	17	1-7/8	48	700
3/8	9-10	17	2	51	1265
7/16	11	35	2-1/8	54	1265
1/2	13	35	2-1/4	56	1410
9/16	14	52	2-3/8	60	1410
5/8	16	52	2-1/2	64	1830
3/4	20	86	2-5/8	67	1830
7/8	22	125	2-3/4	70	2250
1	26	160	3	76	3160
1-1/8	28	210	3-1/4	82	3795
1-1/4	32	350	3-1/2	88	4920
1-3/8	36	350	3-3/4	94	5980
1-1/2	40	420	4	102	7730
1-5/8	42	495	—	—	—

NATO Numbers:

100cc 8030-21-902-1823
 250cc 8030-21-902-1824
 500cc 8030-21-902-1825
 1000cc 8030-21-902-1826

Witnessed and tested by American Bureau of Shipping. (ABS)

Approximate U.S. Measurements:

250cc's Kit 1 Cup
 500cc's Kit 1 Pint
 1000cc's Kit 1 Quart

The hazardous material/dangerous good classification under U.S. DOT, ICAO/IATA and IMO transportation regulations is Resin Solution, flammable liquid class 3, UN1866, packing group III. All shipments made by The Crosby Group, Inc. are under limited quantity packing provisions.