

Grade 80 Alloy Chain

SPECTRUM 8® ALLOY CHAIN



- Alloy Steel.
- Heat Treated.
- Finish - Black Thermadep Coating.
- Permanently embossed with CG (Crosby Group) and 8 (Grade).
- Proof Tested to 2 times the Working Load Limit with certification.

GRADE 80 ALLOY CHAIN recommended for overhead lifting applications.

Chain Size (in.)	Spec.8 Drum Stock No.	Feet Per Drum	Material Size (in.)	Working Load Limit (lbs.)*	Maximum Inside Length (in.)	Minimum Inside Width (in.)	Maximum Length 100 Links (in.)	Weight Per 100 Ft. (lbs.)
9/32 (1/4)	273527	500	.276	3500	.87	.42	90	72
5/16	273536	500	.343	4500	1.01	.49	100	114
3/8	273545	500	.394	7100	1.23	.58	125	148
1/2	273554	300	.512	12000	1.57	.77	164	243
5/8	273563	200	.630	18100	1.93	.90	202	351
3/4	273572	100	.787	28300	2.42	1.14	252	584
7/8	273581	100	.866	34200	2.66	1.26	277	705

* Proof Loaded at 2 times the Working Load Limit. Minimum Ultimate Load is 4 times the Working Load Limit.

**Crosby provides two methods of attaching
Spectrum 8® chain to Crosby fittings**



**A-1337
Lok-A-Loy®
Connecting Link
Refer to Page 194**



**S-1325
Grade 100
Coupler link
Refer to page 203**