

# Lebus® Snatch Blocks



**SEE APPLICATION AND WARNING INFORMATION**

Para Español: [www.thecrosbygroup.com](http://www.thecrosbygroup.com) On Pages 342-349



**L-45-H**

## L-170 Series General Purpose Snatch Blocks

- Hook is Forged Alloy Steel — Quenched and Tempered.
- All parts are forged.
- Opened and closed in seconds without the use of tools.
- Available with hook, shackle or tailboard (pin only).
- Either wire or manila rope may be used.
- Can be furnished with hook latch.
- Blocks furnished with dual rated wireline sheaves.



**L-45-S**



**L-45-T**

Block No.	Bearing Code	L-170 Stock No.	Fitting	Sheave Diam. (in.)	Working Load Limit (t)*	Wire Rope Size (in.)	Manila Rope Size (in.)	Weight Each (lbs.)	Rep. Sheave Stock No.	Rep. Latch Stock No.
L-45-H	BB	599800	Hook	4-1/8	5	3/8 - 1/2	1-1/4	13	460405	1096468
L-45-H	RB	599819	Hook	4-1/8	5	3/8 - 1/2	1-1/4	13	472580	1096468
L-45-S	BB	599828	Shackle	4-1/8	5	3/8 - 1/2	1-1/4	13	460405	-
L-45-S	RB	599837	Shackle	4-1/8	5	3/8 - 1/2	1-1/4	13	472580	-
L-45-T	BB	599846	Tail Board	4-1/8	5	3/8 - 1/2	1-1/4	9	460405	-
L-45-T	RB	599855	Tail Board	4-1/8	5	3/8 - 1/2	1-1/4	9	472580	-

\* Ultimate Load is 4 times the Working Load Limit.

NOTE: When Ordering, specify either roller bearing or bronze bushed sheaves.