

Crosby® Snatch Blocks

SELBY ENGINEERING & LIFTING SAFETY LTD.
Lifting Equipment and Height Safety Specialists
 www.liftingsafety.co.uk sales@liftingsafety.co.uk
 Tel: +44 (0) 1977 684 600 Fax: +44 (0) 1977 685 300

SEE APPLICATION AND WARNING INFORMATION
 Para Español: www.thecrosbygroup.com On Pages 342-349

C-700 SNATCH BLOCKS



General Purpose Snatch Blocks

- Unique locking device permits disengagement by simply folding hook.
- Formed steel side plates with capacity stamped permanently in place.
- Self-Lubricating bronze bushings.
- Can be furnished with S-4320 hook latch.
- Furnished with dual rated wireline sheaves.

Sheave Diam. (in.)	Block No.	C-700 Stock No.	Working Load Limit (Tons)*	Wire Rope Size (in.)	Weight Each (lbs.)	Fitting	Rep. Latch Stock No.
6	10611	260014	2	3/8 - 1/2	12	Swivel Hook	1096468
8	10811	261013	3	1/2 - 5/8	19	Swivel Hook	1096515

* Ultimate Load is 3.5 times the Working Load Limit.

C-720 SNATCH BLOCKS



Heavy Duty Utility Snatch Block

- Forged steel sheaves, bronze bushings.
- Drop forged steel hook.
- Pressure lube fitting.
- Self-locking style. Locks with hook load.
- Can be furnished with S-4320 hook latch.
- Furnished with dual rated wireline sheave.

Sheave Diam. (in.)	Block No.	C-720 Stock No.	Working Load Limit (Tons)*	Wire Rope Size (in.)	Weight Each (lbs.)	Fitting	Rep. Latch Stock No.
6	60611	280010	7	3/4 - 7/8	28	Swivel Hook	1096562

* Ultimate Load is 3.5 times the Working Load Limit.

C-720 TOGGLE BLOCK



Toggle Block (Tail Board)

- Forged steel sheaves, bronze bushings.
- Pressure lube fitting.
- Furnished with dual rated wireline sheave.

Sheave Diam. (in.)	Block No.	C-720 TB Stock No.	Working Load Limit (Tons)*	Wire Rope Size (in.)	Weight Each (lbs.)	Fitting
6	70610	290018	7	3/4 - 7/8	21	Tailboard

* Ultimate Load is 3.5 times the Working Load Limit.