

Western Standard Steel Blocks

SELBY ENGINEERING & LIFTING SAFETY LTD.
 Lifting Equipment and Height Safety Specialists
 www.liftingsafety.co.uk sales@liftingsafety.co.uk
 Tel: +44 (0) 1977 684 600 Fax: +44 (0) 1977 685 300

SEE APPLICATION AND WARNING INFORMATION
 Para Español: www.thecrosbygroup.com On Pages 342-349



HS-262 DOUBLE

Loose Side Hooks with Latch For Manila Rope

- Laser cut side plates
- Grade 5 bolts secured with lock washers and staked nuts.
- Bronze bushed sheaves with larger bearing diameter for extended block life.

Block Size (in.)	Fitting	Manila Rope Size (in.)	Sheave Size (in.)		261 B Stock No.	262 B Stock No.	263 B Stock No.	Working Load Limit (lbs.)*			Weight Each (lbs.)		
			Outside Diam.	Rim Thickness				261 Single	262 Double	263 Triple	261 Single	262 Double	263 Triple
4	HS	1/2	2.25	.63	666826	666229	667228	900	1400	1800	1.38	3.21	3.25
5	HS	5/8	3.00	.75	666844	666247	-	1200	1800	-	2.25	3.88	-
6	HS	3/4	3.50	1.00	666862	666265	-	1800	2500	-	3.75	6.00	-
8	HS	7/8 - 1	4.75	1.13	666906	666309	667308	2800	3800	4800	7.13	10.75	14.75

* Ultimate Load is 3 times the Working Load Limit.



N-411-B

Blocks for Synthetic Fiber Rope with loose swivel hooks

- These blocks are built to carry the increased loads of synthetic fiber ropes.
- All hooks are heat-treated alloy steel.
- You can now use a smaller size rope, and in turn, a smaller block, providing capacities which were previously not possible.

Block Size (in.)	Fitting	411 B* Stock No.	412 B* Stock No.	413 B* Stock No.
4	S	755105	755301	755506
6	S	755123	755329	755524
4	N	757103	757309	757504
6	N	757121	757327	757522

* Bearing Code: B-Self Lubricating Bronze Bushed

Block Size (in.)	Fitting	Sheave Size (in.)			Synthetic Rope Size (in.)	Working Load Limit (lbs.)*			Weight Each (lbs.)		
		Outside Diameter	Rim Thickness	Center Pin Dia.		Single	Double	Triple	Single	Double	Triple
4	S	2.25	.62	.38	1/2	2000	3000	3000	3.00	4.00	6.00
6	S	3.50	1.00	.50	3/4	3000	7000	8000	6.25	10.00	14.00
4	N	2.25	.62	.38	1/2	2000	3000	3000	3.00	4.00	6.00
6	N	3.50	1.00	.50	3/4	3000	4000	6000	6.25	10.00	14.00

* Ultimate Load is 4 times the Working Load Limit.



HW-261B

HW-261 HW-262 5" Steel Blocks

- For 3/8" Diameter Wire Cable.
- Sheave Size: 3 x 3/4 x 3/8".

Block Size (in.)	Fitting	Block Stock No.	Catalog No.	Bearing Type	Wire Rope Size (in.)	Working Load Limit (lbs.)*	Weight Each (lbs.)
5	H	665444	HW261-B	Bronze Bushed	3/8	1200	2
5	H	665462	HW262-B	Bronze Bushed	3/8	1800	4

* Ultimate Load is 3 times the Working Load Limit.



HW-262B