

# Western Blocks for Manila Rope

**SELBY ENGINEERING & LIFTING SAFETY LTD.**  
 Lifting Equipment and Height Safety Specialists  
 www.liftingsafety.co.uk sales@liftingsafety.co.uk  
 Tel: +44 (0) 1977 684 600 Fax: +44 (0) 1977 685 300

**SEE APPLICATION AND WARNING INFORMATION**  
 Para Español: www.thecrosbygroup.com On Pages 342-349

## MANILA ROPE SNATCH BLOCKS



**T-390  
PAINTED**



**T-390  
GALVANIZED**



**T-385  
PAINTED**



**T-385  
GALVANIZED**

### Steel Shell & Wood Shell

- New style blocks feature higher working load limits.
- Painted or Galvanized steel with replaceable wood bumpers.
- Laser cut side plate opens for insertion of wire rope.
- Incorporates exclusive bolt retaining sprint to assure no lost bolts, plus utilizes secondary retaining pin.
- Bronze bushed sheaves with larger bearing diameter for extended block life.
- Utilizes Crosby "N" style hooks with integrated latch.
- Lubricated center pin.
- 10" and 12" sizes utilize steel sheaves.

Block Size (in.)	Fitting	Wood Shell		Steel Shell	
		385-B* Stock No. S.C.	385-B* Stock No. Galv.	390-B* Stock No. S.C.	390-B* Stock No. Galv.
6	T	702000	702108	702216	702324
8	T	702009	702117	702225	702333
10	T	702018	702126	702234	702342
12	T	702027	702135	702243	702351
6	J	702036	702144	702252	702360
8	J	702045	702153	702261	702369
10	J	702054	702162	702270	702378
12	J	702063	702171	702279	702387
6	G	702072	702180	702288	702396
8	G	702081	702189	702297	702405
10	G	702090	702198	702306	702414
12	G	702099	702207	702315	702423

\* Bearing Code: B-Self Lubricating Bronze Bushed, C-Common Iron, R-Roller Bearing

Block Size (in.)	Sheave Size (in.)			Manila Rope Size (in.)	Drop Side	
	Outside Diam.	Rim Thickness	Bearing Diameter		Working Load Limit (Tons)*	Weight Each (lbs.)
6	3.00	.88	.75	3/4 - 7/8	2	7
8	4.00	1.38	1.00	1 - 1-1/8	4	13
10	6.00	1.62	1.50	1-1/4	8	28
12	8.00	1.62	1.50	1-1/2	8	34

\* Ultimate Load is 4 times the Working Load Limit.