

SELBY ENGINEERING AND LIFTING SAFETY LTD 3 LINCOLN WAY, SHERBURN IN ELMET, LEEDS, LS25 6PJ, UK Tel: +44 (0) 1977 684 600 Email: sales@liftingsafety.co.uk LIFTING EQUIPMENT AND HEIGHT SAFETY SPECIALISTS

## Automatic Evacuation Rescue Descender / Fall Arrest Inertia Reel Block

These devices have been manufactured, tested and certified in Germany to conform to the European Standards DIN EN 360 as a retractable type fall arrest device and DIN EN 341 as a descender device for rescue from height.

Specifically developed to offer fall protection and rescue in one, easy to use unit.

Working similar to a car safety belt, during normal use the user can move freely whilst the galvanised steel cable life-line is kept under permanent tension. In the event of a fall the locking system will activate and the internal brake disk will absorb energy to well below the 6kN limit required by the DIN EN 360 standard.

After an arrested fall the device will automatically lower the casualty at an approximate speed of 0.9m/sec.

NOTE: Caution must always be used when employing devices that incorporate an automatic lowering function. Assessment of the cable length required and the ground/landing zone conditions MUST be made prior to use.

## **Product features**

- Easy to use, low-maintenance design
- Load carrying capacity
- > 1 person, 125kg max
- Various cable lengths available
- Shockproof aluminium housing
- Single handed, double action hook to connect to the users harness
- Double action hook has swivel function to eliminate cable twisting
- Large carrying and attachment handle
- World renowned German build quality

## Important

Caution must always be used when employing devices that incorporate an automatic lowering function. Assessment of the cable length required and the ground/landing zone conditions MUST be made prior to use.

Part N°	Model	Cable Length	Weight (kg)	Top Attachment Options
2680-T11965	1FAD-2680-9m	9m	5	None
2680-T11966	1FAD-2680-9m+K	9m	5.15	Supplied with Screwgate Alu. Karabiner
2680-T23584	1FAD-2680-9m+LK	9m	5.36	Supplied with Large "Twist-lock" Steel Karabiner
2680-T23585	1FAD-2680-18m	18m	11	None - Standard Large Carry Handle Only
2680-T23586	1FAD-2680-18m+LK	18m	11.7	Supplied with Large Steel Scaffold Karabiner
2680-T23591	1FAD-2680-30m	30m	15	None - Standard Large Carry Handle Only
2680-T23592	1FAD-2680-30m+LK	30m	15.7	Supplied with Large Steel Scaffold Karabiner

## Accessories

Ontions



Screwgate Alu. Karabiner



Large Steel Scaffold Karabiner



Large "Twist-lock" Steel Karabiner

