



LIFTINGSAFETY

SELBY ENGINEERING AND LIFTING SAFETY LTD

Tel: +44 (0) 1977 684 600 Email: sales@liftingsafety.co.uk

LIFTING EQUIPMENT AND HEIGHT SAFETY SPECIALISTS

6000 KN – Swaging Press

This 6000 KN Two column Swaging Press is capable of pressing the following sizes:

Straight: ZEN 34 (Form A, EN 13411-3)
& up to ZEN 42 in two bite

Rounded: ZEN 34 (Form B, EN 13411-3)

Tapered: ZEN 32 (Form C, EN 13411-3)

Flemish Eye: No.6 – 38



600T P34/40 RFFSC

Quality

This machine is produced in accordance with the CE machinery directive & BS EN 693:2001.

Warranty

This machine comes with a 12 months defective parts warranty.

Technical Data

Solenoid Control Twin Electric Footpedals

Max. pressure capacity	6000 KN
Max. piston stroke	65mm
Max. oil pressure	350 bar

Unloaded stroke speed	10 mm/s
Loaded stroke speed	1.9 mm/s
Reversing speed	12 mm/s
Swaging die take up - Max with angle-packing	110 x 156mm 78 x 100mm

Operating height	1080mm
------------------	--------

Power supply	380 V 50 Hz 11 KW
--------------	-------------------------

Dimensions (LxWxH)	1285 x 1700 x 2000mm
--------------------	-------------------------

Weight	3100 KG
Oil capacity	130 Litres
Oil	ISO VG 32

Other voltage on request.

We reserve the right to change technical data.