

SELBY ENGINEERING AND LIFTING SAFETY LTD. TEL: +44 (0) 1977 684 600

Pfaff-silberblau Hebezeugfabrik GmbH & Co. KG

Äußere Industriestraße 18 Postfach 10 22 33
 86316 Friedberg 86012 Augsburg
 Telefon: 0821 / 78 01 - 0 Telefax: 0821 / 78 01 - 299



Questionnaire Wire-Rope Winches

Numbers of pages:

Customer Number
 Company

Street

ZIP Code

Location/Country.....

Phone ☎

Fax 📠

Contact Person

Position.....

Quantity:

Application of winch: (sketch or installation drawing with dimensions)?

Hoisting winch
 Winch for positioning
 Hauling winch/ recovery winch

Environment:
 Outdoor
 roofed
 corrosive medium _____

Duty cycle:
 S3-40% S3-____%

....Operating factor of load alternation/h
 ... Shift operation (e.g. 2 shifts)
 ... Stroke per load alternation

Technical details:		Explanation (additional):
Lifting capacity (1daN ~ 1 kg)daN	
Rope speed:m/min	<input type="checkbox"/> Infinitely variable rope speed Ratio of control: <input type="checkbox"/> 1:5, (10 -50 Hz) <input type="checkbox"/> 1:9(10 -87 Hz)
Lifting height/ Rope capacity on drumm	
Multilayer winding possible? (Keep in mind the traction force reduction)	<input type="checkbox"/> Yes <input type="checkbox"/> No	
Number of ropes	
Load distribution (at multiple ropes)	
Operation voltage:	<input type="checkbox"/> 3x 230/400 V 50 HzV..... Hz
Motor protection	<input type="checkbox"/> Standard IP 54	<input type="checkbox"/> Type of protection: IP ____
Ambient temperature:	<input type="checkbox"/> Standard -20°C up to +40°C

SELBY ENGINEERING AND LIFTING SAFETY LTD. TEL: +44 (0) 1977 684 600

Pfaff-silberblau Hebezeugfabrik GmbH & Co. KG

Äußere Industriestraße 18
86316 Friedberg
Telefon: 0821 / 78 01 - 0

Postfach 10 22 33
86012 Augsburg
Telefax: 0821 / 78 01 - 299



<input type="checkbox"/> H 01	<input type="checkbox"/> H 02	<input type="checkbox"/> H 03	<input type="checkbox"/> H 04	Rope coiling right	<input type="checkbox"/>	Rope coiling left	<input type="checkbox"/>

Control System:		Yes <input type="checkbox"/>	No <input type="checkbox"/>	on customer site
Standard; according to winch design:		<input type="checkbox"/> integrated in plastic housing with reversing switch and main switch		
Control voltage		<input type="checkbox"/> 42V- 50Hz		
Built-in control elements		<input type="checkbox"/> Basic design		
External hand-actuated auxiliary switch		<input type="checkbox"/>	Up/Down/Emergency-Stop	
External Pendant Control		<input type="checkbox"/>	Up/Down/Emergency-Stop	
Length of control cable		<input type="checkbox"/> 5 m (Standard)	Special lengthm	
Radio control		<input type="checkbox"/>	Range 100 m	
Electronic overload protection		<input type="checkbox"/>	As standard integrated with a lifting capacity of 1 ton or more	

Accessories:		
Gear limit switch	<input type="checkbox"/> 2 switching contacts <input type="checkbox"/> 4 switching contacts	Way of rope:m (4 switching contacts as standard for BGV C1)
Rope pressure drum	<input type="checkbox"/>	
Slack rope switch	<input type="checkbox"/>	
Miscellaneous:		
Wire Rope	<input type="checkbox"/> complete rope length (incl. safety winding on the drum) m Type of rope:.....	
Load hook	<input type="checkbox"/>	
Sheave loose	<input type="checkbox"/> pcs. -Art.-No.	
Wire Rope Pulley Block	<input type="checkbox"/> pcs. -Art.-No.	

Enclosures	
<input type="checkbox"/> Sketch
<input type="checkbox"/> Layout / Drawing No.
<input type="checkbox"/>
<input type="checkbox"/>
<input type="checkbox"/>
Date:
Signature:

Additional information:	Price idea of customer:€
	Rating of success:%
	Competitor:	

Kind of quotation:

SELBY ENGINEERING AND LIFTING SAFETY LTD. TEL: +44 (0) 1977 684 600

Pfaff-silberblau Hebezeugfabrik GmbH & Co. KG

Äußere Industriestraße 18
86316 Friedberg
Telefon: 0821 / 78 01 - 0

Postfach 10 22 33
86012 Augsburg
Telefax: 0821 / 78 01 - 299



<input type="checkbox"/> Abstracted Quotation	<input type="checkbox"/> Target price	<input type="checkbox"/> Quotation untilper			
<input type="checkbox"/> Detailed Quotation	<input type="checkbox"/> Requested delivery date				

LIFTINGSAFETY.CO.UK