

NANO-LOK™ FOR HOT WORK USE

The first ever self retracting lifeline designed for welding, grinding and high heat applications.

DURABLE

Reinforced webbing with Nomex®/ Kevlar® fiber to withstand sparks, weld splatter and other high heat exposure.

VERSATILE

5 different Nano-Lok™ configurations, single and twin-leg, that can be connected at foot level to meet your specific needs.

SAFE

Arc flashed to 8 calories (8 cal/cm²), for hot work use in applications like welding, grinding and torching. Meets or exceeds industry standards. CE EN360:2002.



SWIVELING ANCHORAGE LOOP

DIRECT TO HARNESS WEB ANCHORAGE CONNECTOR

IMPACT-RESISTANT HOUSING

AUTOMATIC QUICK-ACTIVATING FALL ARRESTOR

IMPACT INDICATOR

REINFORCED KEVLAR® WEBBING

HOT WORK ICON TO QUICKLY AND EASILY IDENTIFY HOT WORK PRODUCTS

16 KN (3.600 LB) GATE HOOK

SPECIFICATIONS:

Reinforced webbing with Nomex® / Kevlar® fiber*. Resist to sparks and weld splatters. Arc-flashed resistant to 8 cal / cm²

Certification: CE EN360 : 2002

Capacity: 140 kg

Connection level: Can be connected at foot level

Length = 2 m