

FOLDING CRANE SPECIFICATIONS

Model No.	¼ tonne FFC-773-250	½ tonne FFC-773-500	¾ tonne FFC-773-750	1 tonne FFC-773-1000	1½ tonne FFC-773-1500	2 tonne FFC-773-2000
Capacity Position 1	245 Kg	508 Kg	750 Kg	1000 Kg	1500 Kg	2000 Kg
Capacity Position 2	178 Kg	381 Kg	600 Kg	750 Kg	1250 Kg	1500 Kg
Capacity Position 3	102 Kg	254 Kg	500 Kg	500 Kg	1000 Kg	1000 Kg
Min. Height Hook to Ground (1)	460 mm	460 mm	265 mm	265 mm	450 mm	500 mm
Max. Height Hook to Ground (2)	2270 mm	2270 mm	2235 mm	2235 mm	2550 mm	2720 mm
Column Height (3)	1750 mm	1750 mm	1615 mm	1615 mm	1820 mm	1880 mm
Overall Base Length (4)	1495 mm	1495 mm	1690 mm	1690 mm	1770 mm	1870 mm
Max. Width Between Legs (5)	620 mm	620 mm	790 mm	790 mm	855 mm	960 mm
Max. Overall Width (6)	780 mm	780 mm <td 950 mm	950 mm	1040 mm	1170 mm	
Height to Top of Legs	125 mm	125 mm	130 mm	160 mm	150 mm	225 mm
Diameter of Wheels	100 mm	100 mm	100 mm	125 mm	125 mm	150 mm
Knock Down Height (8)	400 mm	400 mm	610 mm	620 mm	580 mm	660 mm
Weight	85 Kg	85 Kg	100 Kg	130 Kg	200 Kg	210 Kg
LEG STRADDLE ARRANGEMENT						

